



# 9080-Ex Intrinsically Safe Smart Vibration Meter Analyses, Interprets and TRENDS readings...

## BENEFITS

- Find machine faults before they stop your machine
- Increase productivity and lower maintenance costs


## FEATURES

- Collect data
- Trend data using VibTrend software
- Intrinsically Safe cable mounted accelerometer with magnet
- Built-in Bluetooth communication capability
- USB docking station to download to a PC
- ISO built-in Alarms
- Easily identify bearing problems with BDU Reading
- Easily identify problems with built-in band filters:
  - 1X (unbalance)
  - 2X (misalignment)
  - 3X (looseness)
- 800 line FFT (spectrum)
- Ruggedized IP67 case
- 1-year Limited Warranty

PUT THE TPI  
9080-Ex  
TO WORK:

**Commercial & Industrial HVAC**  
**Food Processing**  
**Manufacturing**  
**Mining**  
**Packaging**  
**Petrochemical**  
**Pulp and Paper**  
**Power Plants**  
**Utilities**  
**Automotive**

**VibTrend  
PC Software  
Included as  
Standard**



**Intrinsically Safe  
IEC Ex/ATEX**

**Ex ib IIC T4 Gb  
(-20°C ≤ Ta ≤ +40°C)**

**Identify the vibration  
problem: unbalance,  
misalignment or  
looseness; in addition to  
the bearing condition**

**Intrinsically Safe**

**Certificate Numbers: IECEx BAS 16.0131X Baseefa 16ATEX0182X**






# 9080-Ex Intrinsically Safe Smart Vibration Meter

VibTrend standard software gives you greater ease of use and flexibility. Windows 10™ compatible

- Store analyse and report on all your vibration parameters in one place; unlimited assets with 10 readings per asset with A9084 VibTrend Pro software supplied as standard
- All information is just a click away. Color coded alarms highlight problems. Trend lines show problems before they happen.

Overall machine and bearing conditions: vibration values are displayed with color coded alarm levels for ISO values and Bearing Damage (BDU).




800-line spectrum with zoom and cursor.

- **Size:** H 202mm (7.95") W 60 mm (2.36")
- **Weight:** 280g (9.8oz)
- **Environmental:**
  - ❖ **Water:** IP67 Waterproof
  - ❖ **Operating:** (-20°C ≤ Ta ≤ +40°C)
  - ❖ **Storage:** -20°C to 70°C (-4°F to 158°F)
- **Power supply:** 2xAA batteries (Energizer L91)
- **Battery life:** 2-years standby, 1,500 measurements or approximately 50 hours of normal use
- **Frequency ranges:** ISO: 2/10Hz - 1kHz  
g: 2Hz - 10kHz
- **Frequency resolution:** 100 / 800 lines
- **Displayed amplitude units:** Acceleration in g / velocity in inches per second or mm per second / Bearing damage in BDU
- **Displayed frequency units:** Hz, CPM or RPM
- **Input range:** +/- 60 g
- **Dynamic range:** 96 dB
- **Auto set up of VA bands**
- **Accelerometer connection:** BNC connector cable with removable magnet (1mV/g - 10,000mV/g)
- **Communication:** Bluetooth or USB docking station and cable to PC; data integration using VibTrend software
- **Reading storage:** unlimited assets/10 readings per asset with A9084 VibTrend Pro software as standard
- **Standard accessories:** A9093 Intrinsically Safe accelerometer and magnet, A9081 docking station with USB cable, A9083 VibTrend Standard software and carrying case.

*The 9080-Ex can be used with non-intrinsically safe accessories in non-hazardous areas. Only the 9080-Ex and A9093 intrinsically safe accelerometer should be taken into hazardous areas.*

**VibTrend**  
powerful easy to use  
asset management and  
fault diagnosis  
software



The Vib Meter 9080-Ex and VibTrend is the latest easy to use high specification maintenance tool offering high level functionality and capability at extremely low cost.